



Product data sheet

Toushky U-5100 urethanated Oil

Description

Toushky U-5100 is poly urethane modified soya bean or sun flower oil at 60% solid content.

Application

- *Wood varnishes*
- *Furniture finishes*
- *Parquet sealer*
- *Parquet varnishes*

Features

- *Fast drying*
- *Light color with good yellowing resistance*
- *Abrasion resistance*

Product specification

- | | |
|-----------------------------------|------------------------------------|
| • <i>percent solids, Weigh</i> | <i>60 ±1</i> |
| • <i>Viscosity at 25°C /60%</i> | <i>Z2 -Z3</i> |
| • <i>Type of isocyanate</i> | <i>Aromatic TDI</i> |
| • <i>Color, Gardner</i> | <i>5 max.</i> |
| • <i>Acid value, on solids</i> | <i>2 max.</i> |
| • <i>Oil type</i> | <i>soya bean or sun flower oil</i> |
| • <i>Oil content</i> | <i>67 %</i> |
| • <i>Free iso cyanate content</i> | <i>0 %</i> |
| • <i>Type of polyol</i> | <i>Penta</i> |
| • | |

Storage

- *Store in a dry place at temp.25°C and humidity 55% to ensure a useful shelf life of at least one year.*